



Interior WIFI Pan/Tilt Camera

3mp

3MP WIFI Pan/Tilt Human Tracking Camera

IMC-AL-WIFICAM-PT-3MP



3MP WIFI Pan/Tilt Human Tracking Camera

- 1/2.9" CMOS 3MP 2304x1296
- Lens: 3.6mm (HOV 83.7°, DOV 99°)
- Duplex Two-way Audio
- Full Colour:
 - White LED ON when alarm triggered. IR LED on at 0 Lux
- Pan/Tilt: Horizontal: 360°, Vertical: 130°
- Support AP hotspot
- Support Human Tracking, Motion Detection
- Alarm: Push Notify on APP, Email
- Support SD Card storage (128G Max.)
- Remote video playback
- No external WIFI antenna, simpler appearance
- Lens masking, Privacy protection



Product		Model	IMC-AL-WIFICAM-PT-3MP
System		Chip	T31L
		OS	Embedded Linux
Video		Sensor	1/2.9 CMOS Sensor
		Video encoding	H.264/H.265
		System standard	PAL 50HZ/NTSC 60HZ
		Image	2304*1296 (3MP)
		Pixel	3.0 M pixels
		Video frame rate	15fps
		Video stream	135kbps-2048kbps
		Minimum illumination	Day mode 1Lux, Night mode 0.01Lux
		Day and night mode	Passive mode/day/night/active mode/timing
		DWDR	Support
		Motion Detection	Support
		Capture function	Support
Audio		Encoded standard	G.711U
		Audio input	Passive MIC/active pickup
		Audio output	External 8 Ω /MAX 1.5W speaker
Video management		Video mode	Motion detection recording, alarm recording, timing recording, humanoid recording
		Video save	TF card/NVR



Alarm	Alarm input/output	Not supported
	Alarm triggers	Human form alarm trigger, motion detection alarm, speaker alarm, alarm video, capture, send email
Network	Network antenna	2.4G external antenna
	WIFI protocol	Support 802.11 b/g/n
	WIFI transmission dista	Rectilinear transmission 10m-30m (According to WIFI signal to decide)
	Network protocol	HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP
Other	TF card capacity	Maximum support 128GB (General FAT32 format)
	Voltage	Standard DC-12V (wide voltage 10-16V)
	Current	300mA \pm 10mA
	surroundings	-20 --- +55°C