



Interior WIFI Cube Camera

5mp

3.6mm Lens Pan 355° Tilt 140° 10m Human detection

IMC-AL-WIFICAM5MP



5MP WIFI Cube Camera

- Wide Angle Fixed Lens
- 1/2.8"SONY Starvis Back-illuminated CMOS sensor
- H.265/H.264 Compression rate
- 2 Way Audio
- TF card storage
- IR Range up to 15m
- WIFI 2.4G and LAN
- Supports ONVIF



WIFICAM5MP

Camera

Imaging Sensor	1/2.8 IMX335
System	PAL 50HZ/NTSC 60HZ
Auto Electronic Shutter (AES)	AUTO/ 1/50(1/60)-1/100,000sec
Day & Night	IR Cut Filter auto switch
Lens	2.8mm HOV 105.3°
IR Range	Up to 15M

Video

Max. Resolution	2560*1920 5MP
Main Stream	2560*1920/2560*1440/2048*1536/1920*1080/1280*720
Sub Stream	1280*720/704*576/640*360/352*288
Third Stream	704*576/640*360/352*288
Video Compression	H.265/H.264/MJPEG
Video Stream	128 Kbps-12288kbps (Default VBR)



Network	
Simultaneous Live View	Up to 6 channels
API	ONVIF 2.4
Protocol	HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP
Remote Control	APP, IE browser, Chrome, Firefox
Alarm Trigger	Motion Detection, Humanoid Detection, Email, Capture
Video Recording	Manual, Alarm, Timing
Image	
Day/Night Switch	Day/Night/Auto/Ext
3D DNR	Weak/Normal/Strong is adjustable by web browser
Image Setting	Brightness, Contrast, Saturation, Hue, Sharpness, Gain, are adjustable by web browser
Backlight Compensation (BLC)	ON/OFF is adjustable by web browser
Privacy Masking	4 zones
Interface	
On-Board Storage	TF card slot. Support FAT32 Format TF card (Max.128GB)
Audio I/O	G.711U
Hardware Reset	Yes
Communication	1 RJ45 10M/100M self-adaptive Ethernet port
WIFI Protocol	2.4G IEEE 802.11 B/G/N
WIFI Transmission Distance	No Obstacles 80m Max



General	
Power Supply	DC 12V \pm 10%
Power Consumption	Max. 5W
Working Environment	-10 °C ~50 °C Humidity 95% or less (non-condensing)